

## SZOROWARKA CT70

<b>DANE TECHNICZNE</b>								
		CT70 B55	CT70 BT55	CT70 BT60	CT70 BT70	CT70 BT85	CT70 BT55R	CT70BT70 ECS
Wydajność teoretyczna	m <sup>2</sup> /h	1925	2475	2700	3150	3825	2475	3500
Szerokość robocza	mm	550	550	600	700	850	550	700
Pojemność zbiorników	l	70/75	70/75	70/75	70/75	70/75	70/75	70/75
Czas pracy	min	78	78	78	78	78	78	78
Zasilanie	V-Ah	24(2x12)-105 GEL	24(2x12)-105 GEL	24(2x12)-105 GEL	24(2x12)-105 GEL	24(2x12)-105 GEL	24(2x12)-105 GEL	24(2x12)-105 GEL
Moc maksymalna	W	480	480	480	480	480	480	480
Nacisk szczotek	kg	18,5	18,5	30,5	31,5	31,5	13,6/18,6	15-37
Szerokość ssawy	mm	815	815	815	1010	1010	815	1010
Prędkość maksymalna	km/h	4,5	4,5	4,5	4,5	4,5	4,5	4,5
Waga	kg	85,5	91,5	93,7	94,5	95	100,2	94,5
Wymiary (DłxSzxWys)	mm	1230x587x960	1230x587x960	1210x680xx960	1220,x748x960	12x893x960	1260x893x960	1220x748x1140

<b>PODSTAWOWE AKCESORIA</b>							
<b>SZCZOTKI</b>							
PPL miękka	SPPV01505	SPPV01505	SPPV01473	SPPV01472	SPPV01516		SSV01481
okrągła szczotka – PPL miękka						SPPV01163	
<b>GUMA SSAWY</b>							
guma ssawy przednia	MPVR08039 – 880mm	MPVR08039 – 880mm	MPVR08039 – 880mm	MPVR08040 – 1020mm	MPVR08040 – 1020mm	MPVR08039 – 880mm	MPVR08040 – 1020mm
guma ssawy tylna	MPVR08035 – 900 mm	MPVR08035 – 900 mm	MPVR08035 – 900 mm	MPVR08036 – 1020mm	MPVR08036 – 1020mm	MPVR08035 – 900 mm	MPVR08036 – 1020mm